

1226L

Desktop



12" LCD Touchmonitor

SPECIFICATIONS

Model	1226L	
Case/Bezel color	Gray	
Display type	Active matrix TFT LCD	
Display size	12.1" (30.7 cm) diagonal	
Useful screen area	Horizontal	9.7" (24.6 cm)
	Vertical	7.3" (18.5 cm)
Monitor dimensions	Width	13.4" (34.0 cm)
	Height (including base)	12.8" (32.5 cm)
	Depth (including base)	6.5" (16.6 cm)
Optimal (native) resolution	800 x 600 at 56 or 60 Hz	
Other supported resolutions	640 x 480 at 60, 72, 75, or 80 Hz	
Colors	262,000	
Brightness	LCD panel	100 cd/m ²
	LCD panel with touchscreen	AccuTouch: 75 cd/m ² (typical); IntelliTouch: 92.5 cd/m ² (typical)
Viewing angle (from center)	Horizontal (left/right)	±40° or 80° total
	Vertical (up/down)	10°/30° or 40° total
Contrast ratio	120:1	
Input video format	Analog (no proprietary video card needed)	
Input video signal connector	Mini D-Sub 15-Pin (female); Universal Mac adapter available separately	
Scanning frequency	Horizontal 31.5–43.3 kHz; vertical 56–85 Hz	
Video bandwidth	50 MHz	
Power supply	External power supply, 100–240 VAC, 50–60 Hz	
Power dissipation	20 W max.	
Temperature	Operating 0°C to 40°C; storage –25°C to 60°C	
Humidity	Operating 85%; storage 90%; noncondensing	
Weight (approx.)	Actual 10.7 lb (4.8 kg); shipping 13.3 lb (6.0 kg)	
Warranty	Monitor	1 year
	Touch technology	10 years IntelliTouch touchscreen, 5 years AccuTouch touchscreen
	Touch controller	5 years
	Backlight lamp life	25,000 hours to half brightness
Other features	Digital on-screen display (OSD); removable base; sealing; VESA mounting	

ORDERING INFORMATION

Touch Technology	Touch Interface	Surface Treatment	Elo Part Number	Agency Approvals
AccuTouch	Serial	Antiglare	392863-000	UL, cUL, FCC, CE, TÜV-GS
IntelliTouch	Serial	Antiglare	495919-000	UL, cUL, FCC, CE, TÜV-GS

- Users should independently evaluate the suitability of the product for their application.
- All prices, models, and availability subject to change without notice.

- Stock quantities may be limited. Larger quantities are available within one week.
- For Product Agency Certifications refer to our Web site.