


1266L

Panel Mount



12" LCD Touchmonitor

SPECIFICATIONS

Model	1266L	
Case/Bezel color	Black, metal bezel	
Display type	Active matrix TFT LCD	
Display size	12.1" (30.7 cm) diagonal	
Useful screen area	Horizontal	9.7" (24.6 cm)
	Vertical	7.3" (18.4 cm)
Monitor dimensions	Width	15.2" (38.6 cm)
	Height (including base)	11.4" (29.0 cm)
	Depth (including base)	2.5" (6.3 cm)
Dimensional drawing number	MS500131 (available at www.elotouch.com)	
Optimal (native) resolution	800 x 600 at 60, 70, or 75 Hz	
Other supported resolutions	640 x 480 at 60, 70, or 75 Hz	
Colors	6-bit, 262,144	
Brightness	LCD panel	300 cd/m ²
	LCD panel with touchscreen	AccuTouch: 240 cd/m ² (typical); IntelliTouch/SecureTouch: 275 cd/m ²
Viewing angle (from center)	Horizontal (left/right)	±60° or 120° total
	Vertical (up/down)	+40°/-55° or 95° total
Contrast ratio	200:1	
Input video format	VGA/SVGA analog	
Scanning frequency	Horizontal 25–60 Hz; vertical 56–75 Hz	
Power supply	100–240 VAC, .4 amp max. 50–60 Hz	
Temperature	Operating 0°C to 50°C; storage -25°C to 60°C	
Humidity	Operating 90% noncondensing	
Weight (approx.)	Actual 11.9 lb (5.4 kg); shipping 18.9 lb (8.6 kg)	
Warranty	Monitor	3 years
	Backlight lamp life	50,000 hours at full brightness
Other features	Digital on-screen display (OSD); sealing; remote OSD module	

ORDERING INFORMATION

Touch Technology	Touch Interface	Surface Treatment	Elo Part Number	Agency Approvals
IntelliTouch	Serial	Antiglare	414918-000	UL, cUL, FCC, CE, TÜV
IntelliTouch	USB	Antiglare	692116-000	UL, cUL, FCC, CE, TÜV
SecureTouch 0.25"	Serial	Antiglare	621520-000	UL, cUL, FCC, CE, TÜV
SecureTouch 0.25"	USB	Antiglare	570076-000	UL, cUL, FCC, CE, TÜV
AccuTouch	Serial	Antiglare	499234-000	UL, cUL, FCC, CE, TÜV
AccuTouch	USB	Antiglare	092802-000	UL, cUL, FCC, CE, TÜV

- Users should independently evaluate the suitability of the product for their application.
- All prices, models, and availability subject to change without notice.

- Stock quantities may be limited. Larger quantities are available within one week.
- For Product Agency Certifications refer to our Web site.

12" LCD Touchmonitor

