



17" CRT Touchmonitor

SPECIFICATIONS

Model		1725C
Display size & type		17" (43.18 cm), 16" (40.64 cm) viewable, FST
Dot pitch		0.28 mm
Resolution presets		1280 x 1024 at 65 Hz 1024 x 768 at 85 Hz 1024 x 768 at 75 Hz
Weight (approx.)		Actual 38 lb (17 kg); shipping 46 lb (21kg)
Display area dimensions	default	10.2" (260 mm) H x 7.7" (195 mm) V
	maximum	11.1" (282 mm) H x 8.3" (211 mm) V
Monitor dimensions	width	16.22" (412 mm)
	height	17.2" (436.9 mm)
	depth	16.19" (411.3 mm)
Dimensional drawing number		MS500092 (Available @ www.elotouch.com)
Scanning frequency	horizontal	30–69 kHz
	vertical	47.5–125 Hz
Video bandwidth		108 MHz
Input video power connector		Mini D-Sub 15-pin (female)
Power		90–264 Vac, 50/60 Hz, 90 W (max.)
Elo touchmonitor driver	serial	Compatible with all Elo PC drivers
	USB	98/2000 USB, Win2000
Warranty		2 years monitor, 10 years IntelliTouch screen, 5 years AccuTouch screen, 5 years controller
Additional features		Digital onscreen display controls MPRII, ENERGY STAR, VESA DPMS, VESA DDC 1/2B Plug and Play, ISO 9241/3

ORDERING INFORMATION

Touch Technology	Touch Interface	Surface Treatment	Elo Part Number	Agency Approvals
AccuTouch (5-wire resistive)	Serial	Antiglare	063141-000	UL, cUL, FCC, CE, TÜV-GS
AccuTouch (5-wire resistive)	Serial	Clear	537721-000	UL, cUL, FCC, CE, TÜV-GS
AccuTouch (5-wire resistive)	None	Antiglare	629417-000	UL, cUL, FCC, TÜV-GS
IntelliTouch (surface-wave)	Serial	Antiglare	984333-000	UL, cUL, FCC, CE, TÜV-GS
IntelliTouch (surface-wave)	Serial	Clear	486317-000	UL, cUL, FCC, CE, TÜV-GS
IntelliTouch (surface-wave)	USB	Antiglare	581693-000	UL, cUL, FCC, CE, TÜV-GS

AccuTouch
IntelliTouch

- Users should independently evaluate the suitability of the product for their application.
- All prices, models, and availability subject to change without notice.
- Stock quantities may be limited. Larger quantities are available within one week.
- For Product Agency Certifications refer to our Web site.