

**1767L**

**Panel Mount**



**3000 Series  
17\"/>**

**SPECIFICATIONS**

<b>Model</b>	1767L		
<b>Case/Bezel color</b>	Black anodized metal aluminum (5052-H32) front panel 4.8 mm thick		
<b>Display type</b>	Active matrix TFT LCD		
<b>Display size</b>	17.0" diagonal		
<b>Useful screen area</b>	Horizontal	13.3" (338 mm)	
	Vertical	10.6" (270 mm)	
<b>Monitor dimensions</b>	Width	17.2" (437 mm)/474 mm with brackets)	
	Height (including base)	14.2" (361 mm)	
	Depth (including base)	2.17" (55 mm)	
<b>Dimensional drawing number</b>	MS500238 (Available @ www.elotouch.com)		
<b>Optimal (native) resolution</b>	1280 x 1024 at 75 Hz		
<b>Other supported resolutions</b>	1024 x 768 at 60, 70, or 75 Hz; 832 x 624 at 75 Hz; 832 x 624 at 75 Hz; 800 x 600 at 56, 60, 72, or 75 Hz; 640 x 480 at 66 Hz (Mac); 640 x 480 at 66 Hz (Mac); 640 x 480 at 60, 72, or 75 Hz; 720 x 400 at 70 Hz		
<b>Colors</b>	16.7 million (24 bit)		
<b>Brightness</b>	LCD panel	250 cd/m <sup>2</sup>	
	LCD panel with touchscreen	IntelliTouch: 230 cd/m <sup>2</sup> (typical); AccuTouch: 200 cd/m <sup>2</sup> (typical); SecureTouch: 200 cd/m <sup>2</sup> (typical)	
<b>Viewing angle (from center)</b>	Horizontal (left/right)	±75° or 150°	
	Vertical (up/down)	±70° or 140°	
<b>Contrast ratio</b>	400:1		
<b>Input video format</b>	Analog (no proprietary video card needed) - OR - Digital Video Input (DVI-D)		
<b>Input video signal connector</b>	Mini D-Sub 15-Pin (female)- OR -Digital 19-Pin Input		
<b>Scanning frequency</b>	Horizontal 31.5–80 kHz; vertical 56–75 Hz		
<b>Video bandwidth</b>	135 MHz		
<b>Power supply</b>	External power supply, 100–240 VAC, 50–60 Hz		
<b>Power dissipation</b>	50 W max.		
<b>Temperature</b>	Operating 0°C to 40°C; storage –20°C to 60°C		
<b>Humidity</b>	Operating 20% to 80%; storage 10% to 90%; non-condensing		
<b>Weight (approx.)</b>	Actual 20 lbs. (9.10 kg); shipping 29 lbs. (13.2 kg)		
<b>Warranty</b>	Monitor	3 years	
	Touch technology	5 years AccuTouch touchscreen, 10 years IntelliTouch touchscreen	
	Backlight lamp life	30,000 hours to half brightness	
<b>Other features</b>	Digital on-screen display (OSD); sealing: VESA mounting 75 mm; Remote OSD on 1.8 foot cable; Users controls: • Side: auto, enter, ±, menu, power • OSD: contrast, brightness, H/V position, color, temperature, clock, phase, recall, OSD Time, language (English, German, Spanish, Japanese, French)		

**ORDERING INFORMATION**

Touch Technology	Touch Interface	Surface Treatment	Elo Part Number	Agency Approvals
SecureTouch	Serial	Antiglare	322600-000	UL, cUL, TÜV-BAUART, CE, FCC, IC, VCCI, C-Tick, MPR II
SecureTouch	USB	Antiglare	171864-000	UL, cUL, TÜV-BAUART, CE, FCC, IC, VCCI, C-Tick, MPR II
AccuTouch	Serial	Antiglare	E43160-000	UL, cUL, TÜV-BAUART, CE, FCC, IC, VCCI, C-Tick, MPR II
AccuTouch	USB	Antiglare	A65301-000	UL, cUL, TÜV-BAUART, CE, FCC, IC, VCCI, C-Tick, MPR II
IntelliTouch	Serial	Antiglare	974340-000	UL, cUL, TÜV-BAUART, CE, FCC, IC, VCCI, C-Tick, MPR II
IntelliTouch	USB	Antiglare	358362-000	UL, cUL, TÜV-BAUART, CE, FCC, IC, VCCI, C-Tick, MPR II

- Users should independently evaluate the suitability of the product for their application.
- All prices, models, and availability subject to change without notice.

- Stock quantities may be limited. Larger quantities are available within one week.
- For Product Agency Certifications refer to our Web site.